








# Axpert MAX II Duplex Off-Grid Inverter



- 
-  
- 
- 
- 

- Two independent AC power sources connected and switched automatically
- Status indication with RGB lights
- Maximum PV input current 27A
- Adjustable charging current setting for two different power sources via LCD operation and mobile APP
- Status indication with RGB lights
- Maximum PV input current increases to 27A
- Built-in Wi-Fi for mobile monitoring (Android/iOS App is available)
- Supports USB On-the-Go function
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Built-in anti-dust kit
- Built-in DC output for DC fan, LED bulb, router and so on
- Parallel operation with 6 units

## Axpert MAX II Duplex Off-Grid Inverter Specification

MODEL	Axpert MAX II Duplex 8K	Axpert MAX II Duplex 11K
<b>RATED POWER</b>	8000VA/8000W	11000VA/11000W
<b>PARALLEL CAPABILITY</b>	YES, 6 units	
<b>INPUT</b>		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
<b>OUTPUT</b>		
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
DC Voltage	12 VDC ± 5%, 100W	
<b>BATTERY</b>		
Battery Voltage	48 VDC	48 VDC
Floating Charge Voltage	54 VDC	54 VDC
Overcharge Protection	66 VDC	63 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>		
Maximum PV Array Power	8000W (4000W x 2)	11000W (5500W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum PV Input Current	27A x 2 (MAX 40A)	
Maximum Solar Charge Current	150A	
Maximum AC Charge Current	120A	150A
Maximum Charge Current	150A	
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	147.4x 432.5 x 553.6	
Net Weight (kgs)	18.4	
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact	
<b>OPERATING ENVIRONMENT</b>		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
<b>STANDARD</b>		
Compliance Safety	CE	

Product specifications are subject to change without further notice.